

MATERIAL HEALTH AND SAFETY BULLETIN

| | | | |
|---|--|-----------------------------------|--|
| MANUFACTURER'S NAME | | T.R. INDUSTRIES | |
| STREET ADDRESS | | 11022 VULCAN STREET | |
| CITY, STATE AND ZIP CODE | | SOUTH GATE, CALIFORNIA 90280-0893 | |
| EMERGENCY PHONE NUMBER (24 Hours): | | | |
| Transportation Emergencies Call: CHEMTREC (800) 424-9300 | | | |
| Health Emergencies Call: Los Angeles Poison Information Center (800) 876-4766 | | | |
| PRODUCT: NS-O16/NS-8 NO STREEK GLASS POLISH | CAUTION: Combustible. Contains Petroleum Distillates and Ammonia. Harmful or fatal if swallowed. DO NOT induce vomiting and call a physician. Use in well ventilated area. Avoid eye contact and prolonged skin contact. Keep away from heat sources and open flame. KEEP AWAY FROM CHILDREN. FOR INDUSTRIAL USE. | | |
| CAS NUMBER: (Not Applicable for Blends) | | | |
| DOT (Proper Shipping Name) Compound Cleaner, Non-Hazardous | | | |
| HAZARD RATING NFPA 0-LEAST FIRE - 2 1-SLIGHT TOXICITY - 2 2-MODERATE REACTIVITY - 0 3-HIGH SPECIAL - 4-EXTREME | | | |

| SECTION I .. INGREDIENTS | | | |
|--|--------------|------------------------|--------------|
| PRODUCT | CAS # | TLV | PERCENTAGES |
| MINERAL SPIRITS | 64741-41-9 | 500 | 25-30% |
| PARAFFINS, CYCLOPARAFFINS & AROMATICS | N/A | | 20-25% |
| ISOPROPANOL | 6-76-30 | 400 | 4-6% |
| AQUA AMMONIA | 766-44-17 | 25 | 1-2% |
| DIATOMACEOUS EARTH | 61790-53-2 | 1.15mg/m3 | 5-10% |
| FORMALDEHYDE | 5-00-00 | 400 | .025-.05% |
| WATER EMULSION BLEND | | | 40-45% |
| * Threshold Limit Value | | | |
| A, Osha [] | B, ACGII [] | C, See Section III [] | D, Other [] |
| | | | Cal Osha [] |

Section II .. EMERGENCY AND FIRST AID PROCEDURES

EMERGENCY: Have a physician call: LOS ANGELES POISON INFORMATION CENTER
(24 Hrs.) (800) 876-4766

EYE
CONTACT

Gently flush with large quantities of water for at least 15 minutes. Seek medical attention immediately.

SKIN
CONTACT

Remove any contaminated clothing. Wash with soap and large quantities of water. Seek medical attention if irritated.

INHALATION

If breathing difficulties, dizziness, or light-headedness occur when working in areas with high vapor concentration, move to outside air immediately. If breathing stops, begin artificial respiration and seek immediate medical attention.

INGESTION

If this product is swallowed, seek medical attention immediately. DO NOT induce vomiting unless directed by a physician.

Section III .. PHYSIOLOGICAL EFFECTS AND HEALTH INFORMATION

EYE
EFFECTS

This product may be an eye irritant.

SKIN
EFFECTS

Prolonged skin contact may result in irritation and/or Dermatitis.

SYSTEMIC
EFFECTS

Various studies have shown a possible association with exposure to this product and the following:

CARCINOGEN:NTP IARC MONOGRAPHS OSHA

NONE KNOWN

SECTION IV .. SPECIAL PROTECTION INFORMATION

| | |
|---------------------------------------|--|
| RESPIRATORY PROTECTION (Specify Type) | The use of respiratory protection depends on vapor concentration of the time-weighted TLV. Use a respirator/gas mask with appropriate cartridges and canister (NIOSH approved, if available), or supplied air equipment, depending on airborne concentration. |
| VENTILATION | If general mechanical ventilation proves inadequate to maintain safe vapor concentrations, supplemental local exhaust may be required. Other special precautions, such as respiratory protection, may be required if vapor concentrations cannot be reduced to below the TLV by ventilation. |
| EYE PROTECTION | Safety glasses and/or face shields are recommended. |
| PROTECTIVE GLOVES | The use of heavy rubber gloves is advised to prevent skin irritation and absorption. |
| OTHER PROTECTIVE EQUIPMENT | Impermeable aprons, availability of eye washes and safety are recommended. |

SECTION V .. REACTIVITY DATA

| | |
|--------------------------------------|---|
| STABILITY | Stable |
| Conditions to avoid: | NONE |
| INCOMPATIBILITY (Materials to avoid) | NONE |
| HAZARDOUS DECOMPOSITION PRODUCTS | Thermal decomposition in the presence of air may yield carbon monoxide and/or carbon dioxide. |
| HAZARDOUS POLYMERIZATION | Will Not Occur |

SECTION VI .. SPILL OR LEAK PROCEDURES

HIGHWAY OR RAILWAY SPILLS - CALL CHEMTREC (800) 424-9300

| | |
|---|---|
| PRECAUTIONS IN CASE OF RELEASE OR SPILL | Stay upwind and away from spill unless wearing appropriate protective equipment. Stop and/or contain spill if it can be done safely. Keep all sources of ignition away. |
| WASTE DISPOSAL METHOD | Dispose of product in accordance with applicable local, county, state and Federal regulations. |

SECTION VII .. STORAGE AND SPECIAL PRECAUTIONS

| | |
|----------------------------------|---|
| HANDLING AND STORING PRECAUTIONS | Keep product containers cool, dry and away from sources of ignition. Use and store with adequate ventilation. |
|----------------------------------|---|

| | |
|-------------------|--|
| OTHER PRECAUTIONS | Personnel should avoid inhalation of vapors. Should contact be made, remove saturated clothing and flush with water. |
|-------------------|--|

SECTION VIII .. FIRE AND EXPLOSION HAZARD DATA

| | |
|----------------------------------|--|
| DOT FLAMMABILITY CLASSIFICATION | Flash Point: |
| EXTINGUISHING MEDIA | Use Foam, CO ₂ or dry chemical fire fighting apparatus. |
| UNUSUAL FIRE & EXPLOSION HAZARDS | Keep work areas free of hot metal surfaces and other sources of ignition. |
| HAZARDOUS POLYMERIZATION | The use of self-contained breathing apparatus is recommended for fire fighters. Avoid spreading burning liquid with water. Contact Fire Dept. immediately. |

SECTION IX .. PHYSICAL DATA

| | | |
|--|-------------------------------|------------------------------------|
| Boiling Point: | | |
| Vapor Density: | | |
| EVAPORATION RATE: | Percent Volatile: 57% | Solubility in water: NEGLIGIBLE |
| SPECIFIC GRAVITY: | Weight Per Gallon: 8.2 LBS | |
| APPEARANCE AND ODOR: YELLOWISH GREEN AND HAS A CHARACTERISTIC ODOR. | | |

SECTION X .. DOCUMENTARY INFORMATION

| | | |
|-------------------------------------|-------------------|-----------------------|
| Product Code No. NS-016/NS-8 | Issue date Dec-15 | Prepared By: R.LUKICH |
|-------------------------------------|-------------------|-----------------------|

All information appearing herein is based upon data obtained from the manufacturer and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency. Conditions of use are beyond our control and therefore users are responsible to verify this data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product, or from the publication of use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.