

Toll Free Phone: 800.263.7011  
Toll Free Fax: 800.459.6227

Toll Free Phone: 800.361.3773  
Fax: 905.625.9481



S-39 is a quick acting flux which forms a secure mechanical and electrical bond between solders and metal.

#### Material Specifications

Number	Material(s)
TEMPERATURE RANGE:	0°F (-18°C) to 130°F (54°C)
CONSISTENCY/COLOR:	Viscous Liquid / Clear
SPECIFICATIONS:	Spec.506 C Type 1 Form A
AVAILABLE SIZES:	80 ml and 320 ml
PACKAGE:	Screw cap plastic jar with brush.

- > Works excellent with 40/60, 60/40, 50/50, 95/5 and lead free solders, on copper, brass, galvanized iron, tin,terneplate, zinc, silver, nickel,sheet lead, brass, polished chrome, and some stainless steel.
- > Aggressive and quick acting
- > Water soluble solder flux that is non-acid and lead free
- > Self-Cleaning
- > Water Washable, Odor Free
- > Non-Acid, Lead Free
- > Solders Dissimilar Metals
- > All-Temperature Application
- > Excellent on Tarnished Metal
- > Goes 3X farther than Paste Flux

#### Size and Parts Specifications

Part#	Size	per case
506057	80ml	16
506058	320ml	12