



# Braided Supplies for Faucets



- Nylon-reinforced PVC inner hose
- Stainless steel 304 braiding and ferrule
- Plated brass nuts and inserts
- EPDM washers
- 100% pressure tested
- Logo and lot stamped
- IAPMO (cUPC) certified to CSA B125.6, ASME A112.18.6, NSF-14 and NSF-61
- Max working temperature: 71°C (160°F)
- Max working pressure: 860 kPa (125psi)

<u>Part #</u>	<u>Description</u>	<u>Box Qty</u>
<b>Faucet Supply</b>		
<b>55503</b>	Faucet Braided Supply, 1/2" IPS x 3/8" comp x 9"	10/100
<b>55500</b>	Faucet Braided Supply 1/2" IPS x 3/8" comp x 12"	10/100
<b>55501</b>	Faucet Braided Supply, 1/2" IPS x 3/8" comp x 16"	10/100
<b>55502</b>	Faucet Braided Supply, 1/2" IPS x 3/8" comp x 20"	10/100
<b>55504</b>	Faucet Braided Supply, 1/2" IPS x 3/8" comp x 30"	10/100
<b>Faucet Supply, Specialty</b>		
<b>55506</b>	Faucet Braided Supply, 3/8" OD comp x 3/8" comp x 12"	10/100
<b>55508</b>	Faucet Braided Supply, 3/8" OD comp x 3/8" comp x 20"	10/100
<b>55596</b>	Faucet Braided Supply, 1/2" IPS x 1/2" IPS x 9"	10/100
<b>55597</b>	Faucet Braided Supply, 1/2" IPS x 1/2" IPS x 12"	10/100
<b>55600</b>	Faucet Braided Supply, 1/2" IPS x 1/2" IPS x 48"	10/50

LynCar Inc.- Brampton ON - 800.263.7011 – [www.lyncar.com](http://www.lyncar.com)

Contents are subject to change. Please ensure to obtain the most current information.