

LESS WATER. BETTER PERFORMANCE.



THE RC-RES 3.7K Flat Concealed Residential Sprinkler

NEW Intermediate 205°F Temperature Concealed Sprinkler Added

SAVE 3 GPM for 14' x 14' Maximum Coverage Compared to Any Leading 4.9K Residential Sprinkler

IMPROVED PERFORMANCE with Greater Flexibility for Water Flow and Pressure

- 14 standard cover plate finishes
- Unlimited custom colors and patterns available
- Quick and Easy installation tools
- 3.0, 3.7, 4.9, & 5.8 K-factors for both ordinary and intermediate temperatures

		RC-RES 3.7K		RC-RES 4.9K	
		162 °F (72°C)		162 °F (72°C)	
		NEW 205°F (96°C)		NEW 205°F (96°C)	
Max Coverage	Flow	Pressure	Flow	Pressure	
12' x 12' (3.7m x 3.7m)	10 GPM (37.9 LPM)	7.3 psi (0.50 bar)	13 GPM (49.2 LPM)	7.0 psi (0.48 bar)	
14' x 14' (4.3m x 4.3m)	10 GPM (37.9 LPM)	7.3 psi (0.50 bar)	13 GPM (49.2 LPM)	7.0 psi (0.48 bar)	
15' x 15' (4.6m x 4.6m)	12 GPM (45.4 LPM)	10.5 psi (0.72 bar)	13 GPM (49.2 LPM)	7.0 psi (0.48 bar)	
16' x 16' (4.9m x 4.9m)	13 GPM (49.2 LPM)	12.3 psi (0.85 bar)	13 GPM (49.2 LPM)	7.0 psi (0.48 bar)	

SENJU
SPRINKLER



www.senjuspinkler.com
sales@senjuspinkler.com
949.333.1281

