

NEW FROM

SENJU 
SPRINKLER



FR-RES 4.9K SS4451

FUSIBLE LINK SPRINKLERS

AVAILABLE IN 162°F AND 175°F
WHITE-CHROME-BLACK-BRASS



 949-333-1281

 WWW.SENJUSPRINKLER.COM

Maximum Coverage Area	Ordinary Temperature Rating 162°F (62°C)		Intermediate Temperature Rating 175°F (79°C)		Minimum Spacing
	Minimum Flow	Minimum Pressure	Minimum Flow	Minimum Pressure	
12' X 12' (3.7 m x 3.7 m)	13 GPM	7.0 psi	13 GPM	7.0 psi	8' (2.4m)
14' X 14' (4.3 m x 4.3 m)	13 GPM	7.0 psi	13 GPM	7.0 psi	
15' X 15' (4.6 m x 4.6 m)	13 GPM	7.0 psi	13 GPM	7.0 psi	
16' X 16' (4.9 m x 4.9 m)	14 GPM	8.2 psi	14 GPM	8.2 psi	
18' X 18' (5.5 m x 5.5 m)	17 GPM	12.0 psi	17 GPM	12.0 psi	
20' X 20' (6.1 m x 6.1m)	20 GPM	16.7 psi	20 GPM	16.7 psi	



Maximum Working Pressure: 175psi
Thread Size: 1/2"NPT
Vertical Adjustment: 1/2"